



549.00 EUR

incl. 19% VAT, plus shipping

- 256MB RAM!
- Standalone!
- 800x480 ! 900Mhz !
- FM Modulator!

The CTFPND-6 is a 7" Touchscreen PND on Windows CE 6.0 basis with integrated GPS receiver and RS232 interfaces. Therefor the CTFPND-6 is the perfect plattform for your telematics application. The extra-high native resolution of 800x480 enables a perfect viewing quality.

The device is equipped with a FM transmitter,2x RS232, USB Host and video input. Optionally this device can be equipped with an external TMC receiver.

## Hardware

Memory slot

CPU Prima Dual Core 900Mhz

Flash ROM 128 MB SDRAM 256 MB

TFT LCD 7" Touchscreen

Resolution 800x480

Bluetooth Optional

TMC Optional (GNS module)

Speaker Integrated

SD/SDHC (up to 32GB)



**GPS** 

Video Input

Connector

**FM Transmitter** 

Power

**Dimensions** 

## Software

Operating system

Navigation software

**Features** 

## Scope of supply

Bottom

(a) arresponder

(b) Arresponder

(c) Fight side

(c)

Wendlingen 68

Weiter 64.0 m

Länge: 
Gewicht: 40.0 t

maximale Achslast: 9.0 t

Zurück Abbrechen Weiter

Integrated, SIRFstar III (20 channels)

2x AV input (Rear CAM support, PAL/NTSC)

- SD extension box (optional)
- 2x Serial port
- USB slave
- Rear camera (3.55mm jack)
- AV-In (3.55mm jack)
- SD slot
- External IR (optional)
- USB Host
- Power socket DC
- 3.55mm stereo earphone jack
- Antenna socket for external GPS antenna (additional antenna not included)

Integrated

12/24V DC

190 x 120 x 20 mm

MS Windows CE.NET 6.0 (core version)

PTV TruckNavigator 8.0 (EUROPA)

- Generic RNDIS driver (installed)
- Compact .NET Framework 3.5 (installed)
- CTFPND-6 (7" PND)
- 4GB SD card (with PTV TruckNavigator 8.0 EUROPE)
- 12/24V cigarette-adapter
- 2x RS232 cable (TTL + 12V) [12V power source not included]
- 230V AC Adapter
- PND suction mounting adapter



