



389.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel® Bay Trail Processor J1900 (2.0 GHz) Quad Core
- Support DDR3L 1333MHz Single Channel
- Support 1 \* Serial ATail (3Gb/s) Device
- 4 \* Intel® i211AT PCIe GbE LAN
- 1 \* SIM card holder
- 2 \* Full size mPCIe, 1 \* Full size mPCIe shared with mSATA
- 1 \* External COM (RS232), 1 \* Internal COM (RS232)
- 1 \* External USB3.0, 1 \* USB1.1/2.0, 2 \* Internal USB1.1/2.0
- Support CPU Smart FAN
- Support Watch Dog Timer 0~255 sec
- Lockable +12V DC-in PWR jack

|                     |                                                                                                |
|---------------------|------------------------------------------------------------------------------------------------|
| • Dimension (W*H*D) | • 232 * 152 * 44 mm                                                                            |
| • Product Model     | • JBC130F533XX-1900-G                                                                          |
| • MB model          | • JNF533-1900 (3.5" SBC)                                                                       |
| • CPU               | • INTEL® Bay Trail Processor J1900 (2.0 GHz) Quad Core                                         |
| • BIOS              | • AMI 16MB SMT Flash ROM                                                                       |
| • Memory            | • Up to 8GB DDR3L 1333 MHz                                                                     |
| • Expansion         | • Mini-PCIE * 2 (Full size)<br>• Mini-PCIE with M-SATA * 1 (Full size)                         |
| • Storage           | • 1 * 2.5" SATA HDD<br>• 2 * USB 2.0 Drive<br>• 1 * M-SATA (Full size)                         |
| • Network           | • 4 * RJ45 (Giga Lan)                                                                          |
| • Front I/O Port    | • 2 * Power LED<br>• 1 * HDD LED<br>• 4 * RJ-45<br>• 1 * USB 2.0<br>• 1 * USB 3.0<br>• 1 * COM |

|                 |                                                                                                                                                                      |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • Rear I/O Port | <ul style="list-style-type: none"> <li>• 1 * PW SW</li> <li>• 1 * DC- IN</li> <li>• 6 * WIFI (option)</li> <li>• 1 * VGA (option)</li> <li>• 1 * GND Hold</li> </ul> |
| • Power Source  | • DC-12V                                                                                                                                                             |
| • Certification | <ul style="list-style-type: none"> <li>• EMC : CE , FCC</li> <li>• Safety : RoHS , ErP</li> </ul>                                                                    |
| • Environment   | <ul style="list-style-type: none"> <li>• Operating Temperature : 0 ~ 50°C</li> <li>• Storage Temperature : -10 ~ 70°C</li> </ul>                                     |
| • Packing       | <ul style="list-style-type: none"> <li>• Net Weight■1.8KG</li> <li>• Gross Weight■2.8KG</li> <li>• Color Box Dimension■232(W) x 152 (D) x 44 (H) mm</li> </ul>       |