



409.00 EUR

incl. 19% VAT, plus [shipping](#)

- ASmedia LAN !



- Intel® Bay Trail Processor J1900 (2.0 GHz) Quad Core
- Support DDR3L 1333MHz Single Channel
- Support 1 \* Serial ATAII (3Gb/s) Device
- 4 \* ASmedia PCIe GbE LAN
- 1 \* SIM card holder
- 2 \* mPCIe, 1 \* M.2
- 1 \* External COM (RS232), 1 \* Internal COM (RS232)
- 1 \* External USB3.0, 1 \* USB1.1/2.0, 2 \* Internal USB1.1/2.0
- Support CPU Smart FAN
- Support Watch Dog Timer 0~255 sec
- Lockable +12V DC-in PWR jack

|                |                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------|
| MB Model       | – JNF533MB-1900 / 3.5" SBC                                                                           |
| Part No        | – HBJC130F533M4-19G / HBJC130F533M6-19G (non-WIFI)<br>– HBJC130F533M4W19G / HBJC130F533M6W19G (WIFI) |
| BIOS           | – AMI 64Mb Flash ROM                                                                                 |
| CPU            | – Intel® Bay Trail Processor J1900 (2.0 GHz) Quad Core                                               |
| Memory         | – 1 * DDR3L 1333/1066MHz Single CH up to 8GB                                                         |
| Storage        | – 1 * 2.5" SATA HDD<br>– 2 * USB 2.0 Drive<br>– 1 * M.2 (M-key, 2242)                                |
| Expansion      | – 2 * Mini-PCIe slot (1* full size, 1* half size)<br>– M.2 (M-key, 2242)                             |
| Front I/O Port | – 1 * Power LED<br>– 1 * HDD LED<br>– 4 * RJ-45<br>– 1 * USB 2.0<br>– 1 * USB 3.0<br>– 1 * COM       |

|               |                                                                                                                                                                    |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rear I/O Port | <ul style="list-style-type: none"> <li>– 1 * PW SW</li> <li>– 1 * DC- IN</li> <li>– 6 * WIFI(option)</li> <li>– 1 * VGA(option)</li> <li>– 1 * GND Hold</li> </ul> |
| Power Source  | – 12V DC-in                                                                                                                                                        |
| Compliance    | – CE, FCC, RoHS, ErP                                                                                                                                               |
| Temperature   | <ul style="list-style-type: none"> <li>– Operating Temperature : 0°C~50°C</li> <li>– Storage Temperature : -10°C~70°C</li> </ul>                                   |
| Dimensions    | – 232 (W) *152 (D) * 44 (H) mm                                                                                                                                     |
| Packing       | <ul style="list-style-type: none"> <li>– Net Weight: 1.8KG</li> <li>– Gross Weight■2.8KG</li> <li>– Color Box Dimension■232 (W) x 152 (D) x 44 (H) mm</li> </ul>   |
| Warranty      | – 2 Year limited warranty                                                                                                                                          |