



999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- Integr. Autostart Controller
- Dualchannel VGA

CARTFT.COM



**Support:** [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#) | [Dual-Out-HowTo \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.  
Celeron-M 1.7Ghz is recommended for fanless operation.

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller).

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

| CALU specifications   |                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------|
| Processor (supported) | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher     |
| Memory                | Supports DDR 333/266 DIMM RAM<br>0.8" low profile<br>2x memory slots !<br>Maximum : 2 GB |
| Video                 | Intel Extreme Graphics 2<br>Supports up to 64MB DVMT video memory                        |
| Audio                 | Software AC '97 Audio CODEC                                                              |

|                              |                                                                                                                                                               |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Peripheral Connection</b> | Front :                                                                                                                                                       |
|                              | 1 x IEEE 1394 Firewire port<br>1 x USB 2.0 / 1.1 Port<br>1 x MIC Port<br>1 x Ear Phone output Jack<br>Power-on button<br>Reset button<br>Power-on and HDD LED |
|                              | Rear :                                                                                                                                                        |
|                              | 1 x RS232 COM port<br>1 x RJ45 10/100Mb Fast Ethernet<br>1 x Line-Out output Jack<br>2 x USB 2.0 / 1.1 Ports<br>1 x 15 pin VGA<br>1 x DVI                     |
| <b>Storage</b>               | One 2.5 inch Hard Disk and 9.5mm high.<br>(Support Ultra DMA 33/66/100).                                                                                      |
| <b>Weight &amp; Size</b>     | System approximately 3kg (fully equipped).<br>System Dimension: 155 x 255 x 55 mm                                                                             |
| <b>Power req.</b>            | 9-16VDC, 5A                                                                                                                                                   |
| <b>Accessory</b>             |                                                                                                                                                               |
| <b>Storage</b>               | Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo<br>Supports all 2.5" standard IDE hard drive, ATA-100/66/33.                                   |
| <b>Scope of supply</b>       | Connector cable for Plus, ignition plus and ground<br>Barebone<br>Barebone<br>CPU Kühlkörper                                                                  |

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)