


469.00 EUR
incl. 19% VAT, plus shipping

- Intel J6412 !
- 2 x 2.5GbE !
- 4 x COM !
- Fanless !

- Fanless embedded Box PC with Intel® Celeron® Processor J Series (formerly Elkhart Lake)
- Intel® J6412 with TDP 10W
- Memory: 1 x DDR4 3200/2933MHz, up to 32GB
- High-Speed Networking: 2 x Intel® I225-V 2.5GbE
- Storage: M.2 M-Key with SATA interface and internal 2.5-inch SATA drive bay
- 4K Display: HDMI® 2.0b with up to 4096 x 2160@60Hz

| | |
|---|---|
| SYSTEM | |
| CPU | Intel® Celeron® Processor J Series (formerly Elkhart Lake) |
| CHIPSET | Intel® J6412 (TDP 10W) |
| SYSTEM MEMORY | 1 x DDR4 3200/2933MHz up to 32GB |
| STORAGE DEVICE | 1 x M.2 M key (2242/2280, SATA Interface)<br>1 x 2.5" SATA 6Gb/s internal drive bay (only support 2.5" HDD with a hight ?10mm) |
| POWER | |
| POWER REQUIREMENT | MB : DC-in 12V<br>Adapter : AC100~240V / DC12V_5A_60W |
| DISPLAY | |
| DISPLAY INTERFACE | 1 x HDMI2.0b (Max Resolution : 4096x2160@60Hz) |
| LAN | |
| ETHERNET | 2 x Intel® I225-V, 2.5GbE |
| SYSTEM I/O | |
| REAR I/O | 1 x DC Jack (12V DC-in)<br>4 x COM (4 x RS232 or 2 x RS232 + 2 x RS485)<br>1 x HDMI2.0b<br>2 x USB3.2 Gen.1<br>4 x USB2.0<br>2 x RJ45<br>1 x Line-out<br>1 x MIC<br>1 x Power Button |
| EXPANSION | |
| M.2 | 1 x M.2 E key Socket for WIFI/BT (2230, PCI-Ex1+USB2.0 Interface) |
| MECHANICAL | |

| | |
|---|---|
| MOUNTING | Desktop, Wallmount |
| DIMENSIONS (W x D x H) | 200.0(W) x 180.4 (D) x 59.5 (H) mm |
| ENVIRONMENT & CERTIFICATION | |
| OPERATING TEMPERATURE | -10°C ~ 50°C (14°F ~122°F)<br>(Under the condition of using M.2 interface SSD) |
| STORAGE TEMPERATURE | -20°C ~ 60°C (-4°F ~140°F) |
| OPERATING HUMIDITY | 10 ~ 90% @ 40°C, non-condensing |
| CERTIFICATION | CE/FCC Class A , LVD |