

114.95 EUR
incl. 19% VAT, plus shipping

- 8-Port Gigabit !
- Unmanaged Switch !
- 16 Gbps Switching !
- AT-GS910/8-50 !

The Allied Telesis AT-GS910/8-50 is an unmanaged Gigabit Ethernet switch for desktop and small network environments. It provides eight 10/100/1000T RJ-45 ports and enables simple network expansion with minimal setup requirements.

The switch supports auto-negotiation, auto MDI/MDI-X and half- or full-duplex operation. Features including BPDU and EAP pass-through, flow control, loop guard, jumbo frames and Energy-Efficient Ethernet support reliable and energy-efficient network operation.

Key Features:

- 8x 10/100/1000T Gigabit Ethernet RJ-45 ports
- Unmanaged switch for desktop and small networks
- 16 Gbps switching capacity and 11.9 Mpps throughput
- Auto-negotiation and auto MDI/MDI-X
- Supports BPDU/EAP pass-through, flow control and loop guard
- Supports jumbo frames up to 9216 bytes
- Internal power supply, 100 - 240V AC

Network Interfaces	8x 10/100/1000T RJ-45
Network Media	10 Mbps: Two-pair Category 3 or better unshielded twisted pair cable, maximum 100 m 100 Mbps: Two-pair Category 5 unshielded twisted pair cable, maximum 100 m 1000 Mbps: Four-pair Category 5e unshielded twisted pair cable, maximum 100 m
Standards and compliance	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.3az Energy-Efficient Ethernet
Switching Capacity	16Gbps
Throughput	11.9Mpps
MAC Address Table	Max 4K
Packet Buffer	128Kbytes
Jumbo Frames	9216bytes
Power supply requirements	100 - 240V AC 50 - 60Hz 0.2A
Dimensions (W x D x H)	210 x 121 x 38 mm
Operating Temperature	0-50C (32-122F)

Features	BPDU/EAP pass-through Flow control Loop guard Jumbo Frame Eco-friendly Half/full-duplex Auto-negotiation MDI/MDI-X
Certification	UL60950-1, 2nd Edition CSA C22.2 No.60950-1-07, 2nd Edition IEC60950-1(UL-EU, UL-CB) EAC certification EN55024 ICES Class A VCCI Class A FCC Class A RCM CE EN55022 CISPR 55022 EU RoHS compliant
Mounting	Wall-mount or desktop No bracket